


## SPECIFICATIONS

|                          |   |
|--------------------------|---|
| <b>Height</b>            | 23.875 in.  |
| <b>Width</b>             | 23.875 in.  |
| <b>Area</b>              | 4 sq. ft. (nominal)   |
| <b>Features</b>          | Project 0.48 in. from tile face<br>Recess 1.85 in. from tile face |
| <b>Collection</b>        | Signature   |
| <b>Thickness</b>         | 0.030 in.   |
| <b>Weight</b>            | 12.8 oz. (nominal)  |
| <b>Material</b>          | Rigid vinyl   |
| <b>Color</b>             | Stone   |
| <b>Finish</b>            | Satin   |
| <b>Recessed Lighting</b> | Yes, this style can be used with recessed lighting                |



## INSTALLATION

|                          |  |
|--------------------------|--|
| <b>Installation Type</b> | Standard drop (15/16 to 1 in.)<br>Slimline drop (9/16 in.)                 |
| <b>Borders</b>           | No, border tiles may be required   |
| <b>Strips Required</b>   | Yes, decorative strips or smooth strips required for glue-up installations |
| <b>Direct Mount Grid</b> | No, this product cannot be used with direct mount grid                     |
| <b>Temp. Warning</b>     | Not recommended for installation where ceiling temperatures exceed 120°F   |

## CERTIFICATIONS, LISTINGS, APPROVALS

|                              |                                     |
|------------------------------|-------------------------------------|
| <b>Drop-out Installation</b> | Contact us for information          |
| <b>Fire Ratings</b>          | Class A<br>Euroclass Rating B-s1-d0 |



## PRODUCT DATA SHEET

### Madison Stone Ceiling Tiles

V3-MAD-22STO

---

|                           |   |
|---------------------------|---|
|                           | Flame Class V-0   |
| <b>Code Compliance</b>    | 2015, 2012, 2009, and 2006 IBC                          |
| <b>Indoor Air Quality</b> | Greenguard Gold Certified; low-VOC; dust and fiber free |
| <b>Food Preparation</b>   | FDA and USDA Compliant                                  |
| <b>Moisture</b>           | FEMA Class 4 Material; waterproof; washable             |
| <b>Sustainability</b>     | 100% recyclable   |

## PERFORMANCE

|                            |   |
|----------------------------|---|
| <b>Noise Reduction</b>     | NRC 0.15<br>NRC 0.30 with Soniguard                         |
| <b>Sound Transmission</b>  | STC 15<br>STC 15 with AcoustoTherm<br>STC 18 with Soniguard |
| <b>Ceiling Attenuation</b> | CAC 21<br>CAC 26 with Soniguard                             |
| <b>Thermal Insulation</b>  | R-6.0 with Soniguard  |