

SPECIFICATIONS

| | |
|-------------------|---|
| Height | 23.875 in. |
| Width | 23.875 in. |
| Area | 4 sq. ft. (nominal) |
| Features | Project 0.48 in. from tile face Recess 1.85 in. from tile face |
| Collection | Signature |
| Thickness | 0.030 in. |
| Weight | 12.8 oz. (nominal) |
| Material | Laminated rigid vinyl |
| Color | Sandal Wood |
| Finish | Semi-gloss |
| Recessed | Yes, this style can be used |
| Lighting | with recessed lighting |



INSTALLATION

| | |
|--------------------------|--|
| Installation Type | Standard drop (15/16 to 1 in.) Slimline drop (9/16 in.) |
| Borders | No, border tiles may be required |
| Direct Mount Grid | No, this product cannot be used with direct mount grid |
| Temp. Warning | Not recommended for installation where ceiling temperatures exceed 120°F |

CERTIFICATIONS, LISTINGS, APPROVALS

| | |
|------------------------------|--|
| Drop-out Installation | Contact us for information |
| Fire Ratings | Class A Euroclass Rating B-s1-d0 Flame Class V-0 |



| | |
|---------------------------|---|
| Code Compliance | 2015, 2012, 2009, and 2006 IBC |
| Indoor Air Quality | Greenguard Gold Certified; low-VOC; dust and fiber free |
| Food Preparation | FDA and USDA Compliant |
| Moisture | FEMA Class 4 Material; waterproof; washable |
| Sustainability | 100% recyclable |

PERFORMANCE

| | |
|----------------------------|---|
| Noise Reduction | NRC 0.15 NRC 0.30 with Soniguard |
| Sound Transmission | STC 15 STC 15 with AcoustoTherm STC 18 with Soniguard |
| Ceiling Attenuation | CAC 21 CAC 26 with Soniguard |
| Light Reflectance | 47.62% |
| Thermal Insulation | R-6.0 with Soniguard |