

INSTALLATION INSTRUCTIONS

Ceilume Feather-Light Ceiling Tiles must be suspended by means of an approved ceiling suspension system using standard 1" face t-bar grid, per the manufacturer's instructions for suspension system installation.

IMPORTANT NOTE: No clips, fasteners or impediments of any kind can be used to limit the ceiling tiles' ability to drop from the suspension system without restraint in the event of a fire. Always check local building codes BEFORE installation.

STEP 1



Ceilume Feather-Light Ceiling Tiles and Panels are extremely easy to install. Simply pop any style into place within a standard 1" t-bar grid.


STEP 2



When t-bar grid sections are irregular or not a full 24" x 24" or 24" x 48" in size, Ceilume's edge trim ceiling tile and panel designs can be easily trimmed to fit using common household scissors.

Edge trim ceiling tiles and panels can be used throughout the entire ceiling, or in combination with recessed, projected and hybrid styles.

STEP 3



For best lighting results and optimum life of the tiles and panels, translucent tiles used in lighting applications should be positioned at least 6" from fixtures.

INSTALLATION INSTRUCTIONS

STEP 4



We recommend that translucent ceiling tiles be used in conjunction with AcoustoTherm Backpanels - separate, clear tiles which nest above the ceiling tiles. These backpanels provide better diffusion of light, hide dust and insect accumulation, and increase sound absorption properties.

When installing AcoustoTherm Backpanels, simply set your ceiling tiles into the 1" t-bar grid in pairs: (1) AcoustoTherm Backpanel, convex side up, in combination with (1) Ceilume Smart Ceiling Tile or Panel.

DROP-OUT CEILING TILES UNDER FIRE SPRINKLERS

When installed underneath ceiling fire sprinkler systems, Ceilume Feather-Light Ceiling Tiles, Panels and AcoustoTherm Backpanels must not be fastened directly to metal t-bar members. They are **ONLY** to be set in place in the grid. No clips, fasteners or impediments of any kind can be used to limit the ceiling tiles' ability to drop from the suspension system without restraint in the event of a fire. Always check local building codes **BEFORE** installation.

In areas where tiles are exposed to drafts and air currents, hold down clips can be used, but only to restrict upward movement - clips **MUST NOT** prevent ceiling tiles, panels and backpanels from dropping out in the event of a fire.

CLEANING

Ceilume Feather-Light Ceiling Tiles require no special cleaning agents – just wipe with a soft, damp rag. There is no risk of water damage during cleaning and there is no need for scheduled professional cleaning and resurfacing to prevent environmental and aesthetic problems. Small, stubborn spots can be handled with cleaners such as Fantastik® or Windex®.

Cleaners containing organic solvents or other aggressive ingredients should not be used because they may affect the surface appearance of the tile. Examples of such cleaners are chlorine bleach, liquid grease remover, strong soaps and detergents containing organic solvents, nail polish remover and furniture polish/cleaners.

STORING

Do not store ceiling tiles or panels in direct sunlight or in contact with any heat source that may reach temperatures of over 110 degrees Fahrenheit. When temperatures reach these levels, the vinyl is likely to distort.