

PRODUCT DATA SHEET

Cambridge Cherry Wood Ceiling Tiles

V3-CAMB-22CHY

SPECIFICATIONS

 Height
 23.875 in.

 Width
 23.875 in.

Area 4 sq. ft. (nominal)

Features Project 0.47 in. from tile face

CollectionSignatureThickness0.030 in.

Weight 12.8 oz. (0.20 lb. per sq. ft.)

Material 98% recycled laminated rigid vinyl

Color Cherry Wood
Finish Semi-gloss

Cut-out 6 in. cut-out available

Perforation Available



INSTALLATION

Installation Type Standard drop (15/16 to 1 in.)

Slimline drop (9/16 in.)

Refacing

Glue-up (butt joint)

Borders No, border tiles may be required

Strips Required Yes, decorative strips or smooth strips required for glue-up installations

Direct Mount GridYes, this product may be used with direct mount grid

Temp. Warning Not recommended for installation where ceiling temperatures exceed 120°F

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation Contact us for information



PRODUCT DATA SHEET

Cambridge Cherry Wood Ceiling Tiles

V3-CAMB-22CHY

Fire Ratings Class A

Euroclass Rating B-s1-d0

Flame Class V-0

Code Compliance 2015, 2012, 2009, and 2006 IBC

Indoor Air Quality Greenguard Gold Certified; low-VOC; dust and fiber free

Food Preparation FDA and USDA Compliant

Moisture FEMA Class 4 Material; waterproof; washable

Sustainability Made from 98% recycled material

100% recyclable

PERFORMANCE

Noise Reduction NRC 0.15

NRC 0.30 with Soniguard

Sound Transmission STC 15

STC 15 with AcoustoTherm

STC 18 with Soniguard

Ceiling Attenuation CAC 21

CAC 26 with Soniguard

Light Reflectance 6.67%

Thermal Insulation R-6.0 with Soniguard