

SPECIFICATIONS

Height	23.875 in.
Width	23.875 in.
Area	4 sq. ft. (nominal)
Features	Project 0.47 in. from tile face
Collection	Signature
Thickness	0.030 in.
Weight	12.8 oz. (nominal)
Material	Rigid vinyl
Color	Stone
Finish	Satin
Recessed Lighting	Yes, this style can be used with recessed lighting
Perforation	Available



INSTALLATION

Installation Type	Standard drop (15/16 to 1 in.) Slimline drop (9/16 in.) Refacing Glue-up (butt joint)
Borders	No, border tiles may be required
Strips Required	Yes, decorative strips or smooth strips required for glue-up installations
Direct Mount Grid	Yes, this product can be used with direct mount grid
Temp. Warning	Not recommended for installation where ceiling temperatures exceed 120°F

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation	Contact us for information
------------------------------	----------------------------

Fire Ratings	Class A Euroclass Rating B-s1-d0 Flame Class V-0
Code Compliance	2015, 2012, 2009, and 2006 IBC
Indoor Air Quality	Greenguard Gold Certified; low-VOC; dust and fiber free
Food Preparation	FDA and USDA Compliant
Moisture	FEMA Class 4 Material; waterproof; washable
Sustainability	100% recyclable

PERFORMANCE

Noise Reduction	NRC 0.15 NRC 0.30 with Soniguard
Sound Transmission	STC 15 STC 15 with AcoustoTherm STC 18 with Soniguard
Ceiling Attenuation	CAC 21 CAC 26 with Soniguard
Thermal Insulation	R-6.0 with Soniguard