


SPECIFICATIONS

Height	23.875 in.
Width	23.875 in.
Area	4 sq. ft. (nominal)
Features	Recess 0.25 in. from tile face
Collection	Feather-Light
Thickness	0.013 in.
Weight	6.4 oz. (0.10 lb. per sq. ft.)
Material	Rigid vinyl
Color	Black
Finish	Satin
Recessed Lighting	Yes, this style can be used with recessed lighting
Perforation	Available



INSTALLATION

Installation Type	Standard drop (15/16 to 1 in.)
Borders	Yes, this style can be trimmed for use along borders
Direct Mount Grid	Yes, this product can be used with direct mount grid
Temp. Warning	Not recommended for installation where ceiling temperatures exceed 120°F

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation	Yes, approved for installation <u>beneath</u> fire suppression sprinklers IAPMO Uniform ES Listing Report 5021 IAPMO Uniform ES Evaluation Report 0310 FM Class 4651 FM Certificate of Compliance
------------------------------	---

Fire Ratings	NFPA 13
	UL File R4036
	Class A
	Euroclass Rating B-s2-d0
Code Compliance	Flame Class V-0
	2015, 2012, 2009, and 2006 IBC
Indoor Air Quality	Greenguard Gold Certified; low-VOC; dust and fiber free
Food Preparation	FDA and USDA Compliant
Moisture	FEMA Class 4 Material; waterproof; washable
Sustainability	100% recyclable

PERFORMANCE

Noise Reduction	NRC 0.25
	NRC 0.25 with perforations
	NRC 0.30 with AcoustoTherm
	NRC 0.40 with perforations and AcoustoTherm
	NRC 0.50 with Soniguard
	NRC 0.85 with perforations and Soniguard
Sound Transmission	STC 10
	STC 11 with AcoustoTherm
	STC 13 with Soniguard
Ceiling Attenuation	CAC 14
	CAC 20 with Soniguard
Light Reflectance	5.22%
Thermal Insulation	R-0.012
	R-0.80 with AcoustoTherm
	R-6.0 with Soniguard