


SPECIFICATIONS

Height	23.875 in.
Width	23.875 in.
Area	4 sq. ft. (nominal)
Features	Recess 0.25 in. from tile face
Collection	Feather-Light
Thickness	0.013 in.
Weight	6.4 oz. (0.10 lb. per sq. ft.)
Material	Laminated rigid vinyl
Color	Tin
Finish	Brushed Metallic
Recessed Lighting	Yes, this style can be used with recessed lighting
Perforation	Available



INSTALLATION

Installation Type	Standard drop (15/16 to 1 in.)
Borders	Yes, this style can be trimmed for use along borders
Direct Mount Grid	Yes, this product can be used with direct mount grid
Temp. Warning	Not recommended for installation where ceiling temperatures exceed 120°F

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation	Yes, approved for installation <u>beneath</u> fire suppression sprinklers IAPMO Uniform ES Listing Report 5021 IAPMO Uniform ES Evaluation Report 0310 FM Class 4651 FM Certificate of Compliance
------------------------------	---

Fire Ratings	NFPA 13 Class A Euroclass Rating B-s2-d0 Flame Class V-0
Code Compliance	2015, 2012, 2009, and 2006 IBC
Indoor Air Quality	Greenguard Gold Certified; low-VOC; dust and fiber free
Food Preparation	FDA and USDA Compliant
Moisture	FEMA Class 4 Material; waterproof; washable
Sustainability	100% recyclable

PERFORMANCE

Noise Reduction	NRC 0.25 NRC 0.25 with perforations NRC 0.30 with AcoustoTherm NRC 0.40 with perforations and AcoustoTherm NRC 0.50 with Soniguard NRC 0.85 with perforations and Soniguard
Sound Transmission	STC 10 STC 11 with AcoustoTherm STC 13 with Soniguard
Ceiling Attenuation	CAC 14 CAC 20 with Soniguard
Light Reflectance	36.09%
Thermal Insulation	R-0.012 R-0.80 with AcoustoTherm R-6.0 with Soniguard