

## SPECIFICATIONS

|                          |                                                    |
|--------------------------|----------------------------------------------------|
| <b>Height</b>            | 23.875 in.                                         |
| <b>Width</b>             | 23.875 in.                                         |
| <b>Area</b>              | 4 sq. ft. (nominal)                                |
| <b>Features</b>          | Recess 0.50 in. from tile face                     |
| <b>Collection</b>        | Signature                                          |
| <b>Thickness</b>         | 0.030 in.                                          |
| <b>Weight</b>            | 12.8 oz. (nominal)                                 |
| <b>Material</b>          | 100% recycled rigid vinyl                          |
| <b>Color</b>             | Random Gray                                        |
| <b>Finish</b>            | Satin                                              |
| <b>Recessed Lighting</b> | Yes, this style can be used with recessed lighting |
| <b>Perforation</b>       | Available                                          |



## INSTALLATION

|                          |                                                                          |
|--------------------------|--------------------------------------------------------------------------|
| <b>Installation Type</b> | Standard drop (15/16 to 1 in.)                                           |
| <b>Borders</b>           | No, border tiles may be required                                         |
| <b>Direct Mount Grid</b> | Yes, this product can be used with direct mount grid                     |
| <b>Temp. Warning</b>     | Not recommended for installation where ceiling temperatures exceed 120°F |

## CERTIFICATIONS, LISTINGS, APPROVALS

|                              |                                                        |
|------------------------------|--------------------------------------------------------|
| <b>Drop-out Installation</b> | Contact us for information                             |
| <b>Fire Ratings</b>          | Class A<br>Euroclass Rating B-s1-d0<br>Flame Class V-0 |
| <b>Code Compliance</b>       | 2015, 2012, 2009, and 2006 IBC                         |

---

|                           |                                                         |
|---------------------------|---------------------------------------------------------|
| <b>Indoor Air Quality</b> | Greenguard Gold Certified; low-VOC; dust and fiber free |
| <b>Food Preparation</b>   | FDA and USDA Compliant                                  |
| <b>Moisture</b>           | FEMA Class 4 Material; waterproof; washable             |
| <b>Sustainability</b>     | Made from 100% recycled material<br>100% recyclable     |

## PERFORMANCE

|                            |                                                             |
|----------------------------|-------------------------------------------------------------|
| <b>Noise Reduction</b>     | NRC 0.15<br>NRC 0.30 with Soniguard                         |
| <b>Sound Transmission</b>  | STC 15<br>STC 15 with AcoustoTherm<br>STC 18 with Soniguard |
| <b>Ceiling Attenuation</b> | CAC 21<br>CAC 26 with Soniguard                             |
| <b>Thermal Insulation</b>  | R-6.0 with Soniguard                                        |