


SPECIFICATIONS

Height	23.875 in.
Width	23.875 in.
Area	4 sq. ft. (nominal)
Features	Project 0.09 in. from tile face
Collection	Signature
Thickness	0.030 in.
Weight	12.8 oz. (0.20 lb. per sq. ft.)
Material	98% recycled laminated rigid vinyl
Color	Copper
Finish	Brushed Metallic
Cut-out	6 in. cut-out available



INSTALLATION

Installation Type	Standard drop (15/16 to 1 in.) Slimline drop (9/16 in.) Refacing Glue-up (butt joint)
Borders	Yes, this style may be trimmed for use along borders
Strips Required	Yes, decorative strips or smooth strips required for glue-up installations
Direct Mount Grid	Yes, this product may be used with direct mount grid
Temp. Warning	Not recommended for installation where ceiling temperatures exceed 120°F
Sag Warning	Some minor sagging may occur when used in full-size grid squares

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation	Contact us for information
------------------------------	----------------------------

Fire Ratings	Class A Euroclass Rating B-s1-d0 Flame Class V-0
Code Compliance	2015, 2012, 2009, and 2006 IBC
Indoor Air Quality	Greenguard Gold Certified; low-VOC; dust and fiber free
Food Preparation	FDA and USDA Compliant
Moisture	FEMA Class 4 Material; waterproof; washable
Sustainability	Made from 98% recycled material 100% recyclable

PERFORMANCE

Noise Reduction	NRC 0.15 NRC 0.30 with Soniguard
Sound Transmission	STC 15 STC 15 with AcoustoTherm STC 18 with Soniguard
Ceiling Attenuation	CAC 21 CAC 26 with Soniguard
Light Reflectance	57.46%
Thermal Insulation	R-6.0 with Soniguard