

#### PRODUCT DATA SHEET

# **Evangeline Caramel Wood Ceiling Tiles**

V3-EVANG-22CAR

### **SPECIFICATIONS**

**Height** 23.875 in. **Width** 23.875 in.

Area 4 sq. ft. (nominal)

**Features** Project 0.70 in. from tile face

**Collection** Signature **Thickness** 0.030 in.

Weight 12.8 oz. (nominal)

Material Laminated rigid vinyl

**Color** Caramel Wood

Finish Semi-gloss

**Recessed** Yes, this style can be used **Lighting** with recessed lighting



### **INSTALLATION**

**Installation Type** Standard drop (15/16 to 1 in.)

Slimline drop (9/16 in.)

Refacing

Glue-up (butt joint)

**Borders** No, border tiles may be required

Strips Required Yes, decorative strips or smooth strips required for glue-up installations

**Direct Mount Grid** Yes, this product can be used with direct mount grid

**Temp. Warning** Not recommended for installation where ceiling temperatures exceed 120°F

## **CERTIFICATIONS, LISTINGS, APPROVALS**

**Drop-out Installation** Contact us for information

Fire Ratings Class A



#### PRODUCT DATA SHEET

# **Evangeline Caramel Wood Ceiling Tiles**

V3-EVANG-22CAR

Euroclass Rating B-s1-d0

Flame Class V-0

**Code Compliance** 2015, 2012, 2009, and 2006 IBC

Indoor Air Quality Greenguard Gold Certified; low-VOC; dust and fiber free

**Moisture** FEMA Class 4 Material; waterproof; washable

Sustainability 100% recyclable

### **PERFORMANCE**

Noise Reduction NRC 0.15

NRC 0.30 with Soniguard

Sound Transmission STC 15

STC 15 with AcoustoTherm

STC 18 with Soniguard

Ceiling Attenuation CAC 21

CAC 26 with Soniguard

Light Reflectance 18.93%

Thermal Insulation R-6.0 with Soniguard