

## SPECIFICATIONS

<b>Height</b>	23.875 in.
<b>Width</b>	23.875 in.
<b>Area</b>	4 sq. ft. (nominal)
<b>Features</b>	Project 0.70 in. from tile face
<b>Collection</b>	Signature
<b>Thickness</b>	0.030 in.
<b>Weight</b>	12.8 oz. (nominal)
<b>Material</b>	Rigid vinyl
<b>Color</b>	Sand
<b>Finish</b>	Satin
<b>Recessed Lighting</b>	Yes, this style can be used with recessed lighting



## INSTALLATION

<b>Installation Type</b>	Standard drop (15/16 to 1 in.) Slimline drop (9/16 in.) Refacing Glue-up (butt joint)
<b>Borders</b>	No, border tiles may be required
<b>Strips Required</b>	Yes, decorative strips or smooth strips required for glue-up installations
<b>Direct Mount Grid</b>	Yes, this product can be used with direct mount grid
<b>Temp. Warning</b>	Not recommended for installation where ceiling temperatures exceed 120°F

## CERTIFICATIONS, LISTINGS, APPROVALS

<b>Drop-out Installation</b>	Contact us for information
<b>Fire Ratings</b>	Class A

---

	Euroclass Rating B-s1-d0
	Flame Class V-0
<b>Code Compliance</b>	2015, 2012, 2009, and 2006 IBC
<b>Indoor Air Quality</b>	Greenguard Gold Certified; low-VOC; dust and fiber free
<b>Moisture</b>	FEMA Class 4 Material; waterproof; washable
<b>Sustainability</b>	100% recyclable

## PERFORMANCE

<b>Noise Reduction</b>	NRC 0.15 NRC 0.30 with Soniguard
<b>Sound Transmission</b>	STC 15 STC 15 with AcoustoTherm STC 18 with Soniguard
<b>Ceiling Attenuation</b>	CAC 21 CAC 26 with Soniguard
<b>Light Reflectance</b>	83.88%
<b>Thermal Insulation</b>	R-6.0 with Soniguard