

### PRODUCT DATA SHEET

### **Jackson Cherry Wood Ceiling Tiles**

V3-JACK-22CHY

## **SPECIFICATIONS**

**Height** 23.875 in. **Width** 23.875 in.

Area 4 sq. ft. (nominal)

Features Project 0.38 in. from tile face

**Collection** Signature **Thickness** 0.030 in.

**Weight** 12.8 oz. (0.20 lb. per sq. ft.)

Material 98% recycled laminated rigid vinyl

ColorCherry WoodFinishSemi-glossPerforationAvailable



## **INSTALLATION**

**Installation Type** Standard drop (15/16 to 1 in.)

Slimline drop (9/16 in.)

Refacing

Glue-up (butt joint)

**Borders** No, border tiles may be required

**Strips Required** Yes, decorative strips or smooth strips required for glue-up installations

**Direct Mount Grid** Yes, this product may be used with direct mount grid

Temp. Warning Not recommended for installation where ceiling temperatures exceed 120°F

# **CERTIFICATIONS, LISTINGS, APPROVALS**

**Drop-out Installation** Contact us for information

Fire Ratings Class A



### PRODUCT DATA SHEET

### **Jackson Cherry Wood Ceiling Tiles**

V3-JACK-22CHY

Euroclass Rating B-s1-d0

Flame Class V-0

**Code Compliance** 2015, 2012, 2009, and 2006 IBC

Indoor Air Quality Greenguard Gold Certified; low-VOC; dust and fiber free

Food Preparation FDA and USDA Compliant

Moisture FEMA Class 4 Material; waterproof; washable

Sustainability Made from 98% recycled material

100% recyclable

# **PERFORMANCE**

Noise Reduction NRC 0.15

NRC 0.30 with Soniguard

Sound Transmission STC 15

STC 15 with AcoustoTherm

STC 18 with Soniguard

Ceiling Attenuation CAC 21

CAC 26 with Soniguard

Light Reflectance 6.67%

Thermal Insulation R-6.0 with Soniguard