Ceilume

PRODUCT DATA SHEET Lafayette Sand Ceiling Tiles

V3-LAF-22SAO

SPECIFICATIONS

Height	23.875 in.
Width	23.875 in.
Area	4 sq. ft. (nominal)
Practical Coverage Area	3.47 sq. ft.
Features	Project 0.17 in. from tile face
Collection	Signature
Thickness	0.030 in.
Weight	12.8 oz. (nominal)
Material	Rigid vinyl
Color	Sand
Finish	Satin



INSTALLATION

Installation Type	Glue-up (lap joint)
	Suitable for wall installation
Borders	Yes, this style can be trimmed for use along borders
Strips Required	No, this tile has an overlapping edge feature and no strips are required.
Temp. Warning	Do not install where temperature exceeds 140°F and keep heat sources 6 in. from tile surface.

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation	Contact us for information
Fire Ratings	Class A
	Euroclass Rating B-s1-d0
	Flame Class V-0

PRODUCT DATA SHEET Lafayette Sand Ceiling Tiles

V3-LAF-22SAO

Indoor Air Quality	Greenguard Gold Certified; low-VOC; dust and fiber free
Moisture	FEMA Class 4 Material; waterproof; washable
Sustainability	100% recyclable

PERFORMANCE

Light Reflectance 83.88%