

PRODUCT DATA SHEET

Madison Caramel Wood Ceiling Tiles

V3-MAD-22CAR

SPECIFICATIONS

Height 23.875 in. **Width** 23.875 in.

Area 4 sq. ft. (nominal)

Features Project 0.48 in. from tile face

Recess 1.85 in. from tile face

Collection Signature **Thickness** 0.030 in.

Weight 12.8 oz. (0.20 lb. per sq. ft.)

Material Laminated rigid vinyl

Color Caramel Wood

Finish Semi-gloss

Cut-out 6 in. cut-out available



INSTALLATION

Installation Type Standard drop (15/16 to 1 in.)

Slimline drop (9/16 in.)

Borders No, border tiles may be required

Direct Mount GridNo, this product may not be used with direct mount grid

Temp. Warning Not recommended for installation where ceiling temperatures exceed 120°F

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation Contact us for information

Fire Ratings Class A

Euroclass Rating B-s1-d0

Flame Class V-0



PRODUCT DATA SHEET

Madison Caramel Wood Ceiling Tiles

V3-MAD-22CAR

Code Compliance 2015, 2012, 2009, and 2006 IBC

Indoor Air Quality Greenguard Gold Certified; low-VOC; dust and fiber free

Food Preparation FDA and USDA Compliant

Moisture FEMA Class 4 Material; waterproof; washable

Sustainability 100% recyclable

PERFORMANCE

Noise Reduction NRC 0.15

NRC 0.30 with Soniguard

Sound Transmission STC 15

STC 15 with AcoustoTherm

STC 18 with Soniguard

Ceiling Attenuation CAC 21

CAC 26 with Soniguard

Light Reflectance 18.93%

Thermal Insulation R-6.0 with Soniguard