

PRODUCT DATA SHEET

Mirage Merlot Ceiling Tiles

V3-MIR-22MEO

SPECIFICATIONS

Height 23.875 in. **Width** 23.875 in.

Area 4 sq. ft. (nominal)

Features Recess 0.50 in. from tile face


Collection Signature **Thickness** 0.030 in.

Weight 12.8 oz. (0.20 lb. per sq. ft.)

MaterialRigid vinylColorMerlotFinishSatin

Cut-out 6 in. cut-out available

Perforation Available



INSTALLATION

Installation Type Standard drop (15/16 to 1 in.)

Borders No, border tiles may be required

Direct Mount Grid Yes, this product may be used with direct mount grid

Temp. Warning Not recommended for installation where ceiling temperatures exceed 120°F

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation Contact us for information

Fire Ratings Class A

Euroclass Rating B-s1-d0

Flame Class V-0

Code Compliance 2015, 2012, 2009, and 2006 IBC



PRODUCT DATA SHEET

Mirage Merlot Ceiling Tiles

V3-MIR-22MEO

Indoor Air Quality Greenguard Gold Certified; low-VOC; dust and fiber free

Food Preparation FDA and USDA Compliant

Moisture FEMA Class 4 Material; waterproof; washable

Sustainability 100% recyclable

PERFORMANCE

Noise Reduction NRC 0.15

NRC 0.30 with Soniguard

Sound Transmission STC 15

STC 15 with AcoustoTherm

STC 18 with Soniguard

Ceiling Attenuation CAC 21

CAC 26 with Soniguard

Light Reflectance 6.97%

Thermal Insulation R-6.0 with Soniguard