

## SPECIFICATIONS

|                                |                                 |
|--------------------------------|---------------------------------|
| <b>Height</b>                  | 23.875 in.                      |
| <b>Width</b>                   | 23.875 in.                      |
| <b>Area</b>                    | 4 sq. ft. (nominal)             |
| <b>Practical Coverage Area</b> | 3.47 sq. ft.                    |
| <b>Features</b>                | Project 0.11 in. from tile face |
| <b>Collection</b>              | Signature                       |
| <b>Thickness</b>               | 0.030 in.                       |
| <b>Weight</b>                  | 12.8 oz. (nominal)              |
| <b>Material</b>                | Rigid vinyl                     |
| <b>Color</b>                   | Merlot                          |
| <b>Finish</b>                  | Satin                           |



## INSTALLATION

|                          |                                                                                               |
|--------------------------|-----------------------------------------------------------------------------------------------|
| <b>Installation Type</b> | Glue-up (lap joint)<br>Suitable for wall installation                                         |
| <b>Borders</b>           | Yes, this style can be trimmed for use along borders                                          |
| <b>Strips Required</b>   | No, this tile has an overlapping edge feature and no strips are required.                     |
| <b>Temp. Warning</b>     | Do not install where temperature exceeds 140°F and keep heat sources 6 in. from tile surface. |

## CERTIFICATIONS, LISTINGS, APPROVALS

|                              |                                                        |
|------------------------------|--------------------------------------------------------|
| <b>Drop-out Installation</b> | Contact us for information                             |
| <b>Fire Ratings</b>          | Class A<br>Euroclass Rating B-s1-d0<br>Flame Class V-0 |



---

|                           |                                                         |
|---------------------------|---------------------------------------------------------|
| <b>Indoor Air Quality</b> | Greenguard Gold Certified; low-VOC; dust and fiber free |
| <b>Moisture</b>           | FEMA Class 4 Material; waterproof; washable             |
| <b>Sustainability</b>     | 100% recyclable                                         |

## PERFORMANCE

|                          |       |
|--------------------------|-------|
| <b>Light Reflectance</b> | 6.97% |
|--------------------------|-------|