

PRODUCT DATA SHEET

Nantucket Sand Ceiling Tiles

V3-NAN-22SAO

SPECIFICATIONS

Height 23.875 in. **Width** 23.875 in.

Area 4 sq. ft. (nominal)

Practical

Coverage Area

3.47 sq. ft.

Features Project 0.11 in. from tile face

Collection Signature **Thickness** 0.030 in.

Weight 12.8 oz. (nominal)

Material Rigid vinyl

Color Sand Finish Satin



INSTALLATION

Installation Type Glue-up (lap joint)

Suitable for wall installation

Borders Yes, this style can be trimmed for use along borders

Strips Required No, this tile has an overlapping edge feature and no strips are required.

Temp. Warning

Do not install where temperature exceeds 140°F and keep heat sources 6 in. from

tile surface.

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation Contact us for information

Fire Ratings Class A

Euroclass Rating B-s1-d0

Flame Class V-0



PRODUCT DATA SHEET

Nantucket Sand Ceiling Tiles

V3-NAN-22SAO

Indoor Air Quality Greenguard Gold Certified; low-VOC; dust and fiber free

Moisture FEMA Class 4 Material; waterproof; washable

Sustainability 100% recyclable

PERFORMANCE

Light Reflectance 83.88%