

## SPECIFICATIONS

<b>Height</b>	23.875 in.
<b>Width</b>	23.875 in.
<b>Area</b>	4 sq. ft. (nominal)
<b>Practical Coverage Area</b>	3.47 sq. ft.
<b>Features</b>	Project 0.11 in. from tile face
<b>Collection</b>	Signature
<b>Thickness</b>	0.030 in.
<b>Weight</b>	12.8 oz. (nominal)
<b>Material</b>	Laminated rigid vinyl
<b>Color</b>	Sandal Wood
<b>Finish</b>	Semi-gloss



## INSTALLATION

<b>Installation Type</b>	Glue-up (lap joint) Suitable for wall installation
<b>Borders</b>	Yes, this style can be trimmed for use along borders
<b>Strips Required</b>	No, this tile has an overlapping edge feature and no strips are required.
<b>Temp. Warning</b>	Do not install where temperature exceeds 140°F and keep heat sources 6 in. from tile surface.

## CERTIFICATIONS, LISTINGS, APPROVALS

<b>Drop-out Installation</b>	Contact us for information
<b>Fire Ratings</b>	Class A Euroclass Rating B-s1-d0 Flame Class V-0



## PRODUCT DATA SHEET

Nantucket Sandal Wood Ceiling Tiles

V3-NAN-22SWD

---

<b>Indoor Air Quality</b>	Greenguard Gold Certified; low-VOC; dust and fiber free
<b>Moisture</b>	FEMA Class 4 Material; waterproof; washable
<b>Sustainability</b>	100% recyclable

## PERFORMANCE

<b>Light Reflectance</b>	47.62%
--------------------------	--------