

SPECIFICATIONS

| | |
|--------------------------|--|
| Height | 23.875 in. |
| Width | 23.875 in. |
| Area | 4 sq. ft. (nominal) |
| Features | Recess 0.50 in. from tile face |
| Collection | Signature |
| Thickness | 0.030 in. |
| Weight | 12.8 oz. (nominal) |
| Material | Rigid vinyl |
| Color | Stone |
| Finish | Satin |
| Recessed Lighting | Yes, this style can be used with recessed lighting |
| Perforation | Available |



INSTALLATION

| | |
|--------------------------|--|
| Installation Type | Standard drop (15/16 to 1 in.) Slimline drop (9/16 in.) |
| Borders | Yes, this style can be trimmed for use along borders |
| Strips Required | Yes, decorative strips or smooth strips required for glue-up installations |
| Direct Mount Grid | Yes, this product can be used with direct mount grid |
| Temp. Warning | Not recommended for installation where ceiling temperatures exceed 120°F |

CERTIFICATIONS, LISTINGS, APPROVALS

| | |
|------------------------------|--|
| Drop-out Installation | Yes, approved for installation <u>beneath</u> fire suppression sprinklers IAPMO Uniform ES Listing Report 5021 IAPMO Uniform ES Evaluation Report 0310 |
|------------------------------|--|

| | |
|---------------------------|---|
| Fire Ratings | Class A Euroclass Rating B-s1-d0 Flame Class V-0 |
| Code Compliance | 2015, 2012, 2009, and 2006 IBC |
| Indoor Air Quality | Greenguard Gold Certified; low-VOC; dust and fiber free |
| Food Preparation | FDA and USDA Compliant |
| Moisture | FEMA Class 4 Material; waterproof; washable |
| Sustainability | 100% recyclable |

PERFORMANCE

| | |
|----------------------------|---|
| Noise Reduction | NRC 0.15 NRC 0.30 with Soniguard |
| Sound Transmission | STC 15 STC 15 with AcoustoTherm STC 18 with Soniguard |
| Ceiling Attenuation | CAC 21 CAC 26 with Soniguard |
| Thermal Insulation | R-6.0 with Soniguard |