

### PRODUCT DATA SHEET

### Oxford Cherry Wood Ceiling Tiles

V3-OX-24CHY

## **SPECIFICATIONS**

**Height** 47.875 in. **Width** 23.875 in.

Area 8 sq. ft. (nominal)

Features Recess 0.50 in. from tile face

**Collection** Signature **Thickness** 0.030 in.

**Weight** 25.6 oz. (0.20 lb. per sq. ft.)

Material 98% recycled laminated rigid vinyl

Color Cherry Wood
Finish Semi-gloss

**Cut-out** 6 in. cut-out available



## **INSTALLATION**

**Installation Type** Standard drop (15/16 to 1 in.)

Slimline drop (9/16 in.)

Borders Yes, this style may be trimmed for use along borders

Direct Mount Grid Yes, this product may be used with direct mount grid

**Temp. Warning** Not recommended for installation where ceiling temperatures exceed 120°F

# **CERTIFICATIONS, LISTINGS, APPROVALS**

**Drop-out Installation** Yes, approved for installation <u>beneath</u> fire suppression sprinklers

IAPMO Uniform ES Listing Report 5021

IAPMO Uniform ES Evaluation Report 0310 CertMark Evaluation Report CMI-ER31001

Fire Ratings Class A



### PRODUCT DATA SHEET

## Oxford Cherry Wood Ceiling Tiles

V3-OX-24CHY

Euroclass Rating B-s1-d0

Flame Class V-0

**Code Compliance** 2015, 2012, 2009, and 2006 IBC

Indoor Air Quality Greenguard Gold Certified; low-VOC; dust and fiber free

Food Preparation FDA and USDA Compliant

Moisture FEMA Class 4 Material; waterproof; washable

Sustainability Made from 98% recycled material

100% recyclable

# **PERFORMANCE**

Noise Reduction NRC 0.15

NRC 0.30 with Soniguard

Sound Transmission STC 15

STC 15 with AcoustoTherm

STC 18 with Soniguard

Ceiling Attenuation CAC 21

CAC 26 with Soniguard

Light Reflectance 6.67%

Thermal Insulation R-6.0 with Soniguard