


## SPECIFICATIONS

<b>Height</b>	23.875 in.
<b>Width</b>	23.875 in.
<b>Area</b>	4 sq. ft. (nominal)
<b>Features</b>	Project 0.13 in. from tile face Recess 0.23 in. from tile face
<b>Collection</b>	Feather-Light
<b>Thickness</b>	0.013 in.
<b>Weight</b>	6.4 oz. (0.10 lb. per sq. ft.)
<b>Material</b>	Rigid vinyl
<b>Color</b>	Black
<b>Finish</b>	Satin



## INSTALLATION

<b>Installation Type</b>	Standard drop (15/16 to 1 in.)
<b>Borders</b>	Yes, this style can be trimmed for use along borders
<b>Direct Mount Grid</b>	Yes, this product can be used with direct mount grid
<b>Temp. Warning</b>	Not recommended for installation where ceiling temperatures exceed 120°F

## CERTIFICATIONS, LISTINGS, APPROVALS

<b>Drop-out Installation</b>	Yes, approved for installation <u>beneath</u> fire suppression sprinklers IAPMO Uniform ES Listing Report 5021 IAPMO Uniform ES Evaluation Report 0310 FM Class 4651 FM Certificate of Compliance NFPA 13
------------------------------	--

---

	UL File R4036
<b>Fire Ratings</b>	Class A Euroclass Rating B-s2-d0 Flame Class V-0
<b>Code Compliance</b>	2015, 2012, 2009, and 2006 IBC
<b>Indoor Air Quality</b>	Greenguard Gold Certified; low-VOC; dust and fiber free
<b>Moisture</b>	FEMA Class 4 Material; waterproof; washable
<b>Sustainability</b>	100% recyclable

## PERFORMANCE

<b>Noise Reduction</b>	NRC 0.25 NRC 0.30 with AcoustoTherm NRC 0.50 with Soniguard
<b>Sound Transmission</b>	STC 10 STC 11 with AcoustoTherm STC 13 with Soniguard
<b>Ceiling Attenuation</b>	CAC 14 CAC 20 with Soniguard
<b>Light Reflectance</b>	5.22%
<b>Thermal Insulation</b>	R-0.012 R-0.80 with AcoustoTherm R-6.0 with Soniguard