# Ceilume

#### **PRODUCT DATA SHEET** Rattan Bronze Ceiling Tiles

V3-RATTAN-22BBR

### **SPECIFICATIONS**

| Height               | 23.875 in.   |  |
|----------------------|--|--|
| Width                | 23.875 in.   |  |
| Area                 | 4 sq. ft. (nominal)                                |  |
| Features             | Project 0.11 in. from tile face                    |  |
| Collection           | Signature  |  |
| Thickness            | 0.030 in.  |  |
| Weight               | 12.8 oz. (nominal)                                 |  |
| Material             | 98% recycled laminated rigid vinyl                 |  |
| Color                | Bronze   |  |
| Finish               | Brushed Metallic                                   |  |
| Recessed<br>Lighting | Yes, this style can be used with recessed lighting |  |



### **INSTALLATION**

| Installation Type | Standard drop (15/16 to 1 in.)   |  |
|-------------------|--|--|
|                   | Slimline drop (9/16 in.)   |  |
|                   | Refacing   |  |
|                   | Glue-up (butt joint)   |  |
| Borders           | Yes, this style can be trimmed for use along borders                       |  |
| Strips Required   | Yes, decorative strips or smooth strips required for glue-up installations |  |
| Direct Mount Grid | Yes, this product can be used with direct mount grid                       |  |
| Temp. Warning     | Not recommended for installation where ceiling temperatures exceed 120°F   |  |
| Sag Warning       | Some minor sagging can occur when used in full-size grid squares           |  |

## **CERTIFICATIONS, LISTINGS, APPROVALS**

Drop-out Installation Contact us for information

## Ceilume

#### **PRODUCT DATA SHEET** Rattan Bronze Ceiling Tiles

V3-RATTAN-22BBR

| Fire Ratings       | Class A   |  |
|--------------------|---|--|
|                    | Euroclass Rating B-s1-d0                                |  |
|                    | Flame Class V-0   |  |
| Code Compliance    | 2015, 2012, 2009, and 2006 IBC                          |  |
| Indoor Air Quality | Greenguard Gold Certified; low-VOC; dust and fiber free |  |
| Moisture           | FEMA Class 4 Material; waterproof; washable             |  |
| Sustainability     | Made from 98% recycled material                         |  |
|                    | 100% recyclable   |  |

#### PERFORMANCE

| Noise Reduction     | NRC 0.15                 |
|---------------------|--------------------------|
|                     | NRC 0.30 with Soniguard  |
| Sound Transmission  | STC 15                   |
|                     | STC 15 with AcoustoTherm |
|                     | STC 18 with Soniguard    |
| Ceiling Attenuation | CAC 21                   |
|                     | CAC 26 with Soniguard    |
| Light Reflectance   | 11.43%                   |
| Thermal Insulation  | R-6.0 with Soniguard     |