

PRODUCT DATA SHEET

Rattan Tin Ceiling Tiles

V3-RATTAN-22PBR

SPECIFICATIONS

 Height
 23.875 in.

 Width
 23.875 in.

Area 4 sq. ft. (nominal)

Features Project 0.11 in. from tile face

Collection Signature **Thickness** 0.030 in.


Weight 12.8 oz. (nominal)

Material 98% recycled laminated rigid vinyl

Color Tin

Finish Brushed Metallic

Recessed Yes, this style can be used **Lighting** with recessed lighting



INSTALLATION

Installation Type Standard drop (15/16 to 1 in.)

Slimline drop (9/16 in.)

Refacing

Glue-up (butt joint)

Borders Yes, this style can be trimmed for use along borders

Strips Required Yes, decorative strips or smooth strips required for glue-up installations

Direct Mount Grid Yes, this product can be used with direct mount grid

Temp. Warning Not recommended for installation where ceiling temperatures exceed 120°F

Sag Warning Some minor sagging can occur when used in full-size grid squares

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation Contact us for information



PRODUCT DATA SHEET

Rattan Tin Ceiling Tiles

V3-RATTAN-22PBR

Fire Ratings Class A

Euroclass Rating B-s1-d0

Flame Class V-0

Code Compliance 2015, 2012, 2009, and 2006 IBC

Indoor Air Quality Greenguard Gold Certified; low-VOC; dust and fiber free

Moisture FEMA Class 4 Material; waterproof; washable

Sustainability Made from 98% recycled material

100% recyclable

PERFORMANCE

Noise Reduction NRC 0.15

NRC 0.30 with Soniguard

Sound Transmission STC 15

STC 15 with AcoustoTherm

STC 18 with Soniguard

Ceiling Attenuation CAC 21

CAC 26 with Soniguard

Light Reflectance 36.09%

Thermal Insulation R-6.0 with Soniguard