Ceilume

PRODUCT DATA SHEET Sahara Merlot Ceiling Tiles

V3-SAHARA-22MEO

SPECIFICATIONS

Height	23.875 in.	
Width	23.875 in.	
Area	4 sq. ft. (nominal)	
Features	Project 0.11 in. from tile face	
Collection	Signature	
Thickness	0.030 in.	
Weight	12.8 oz. (nominal)	
Material	Rigid vinyl	
Color	Merlot	
Finish	Satin	
Recessed Lighting	Yes, this style can be used with recessed lighting	



INSTALLATION

Installation Type	Standard drop (15/16 to 1 in.)	
	Slimline drop (9/16 in.)	
	Refacing	
	Glue-up (butt joint)	
Borders	Yes, this style can be trimmed for use along borders	
Strips Required	Yes, decorative strips or smooth strips required for glue-up installations	
Direct Mount Grid	Yes, this product can be used with direct mount grid	
Temp. Warning	Not recommended for installation where ceiling temperatures exceed 120°F	
Sag Warning	Some minor sagging can occur when used in full-size grid squares	

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation Contact us for information

Ceilume

PRODUCT DATA SHEET Sahara Merlot Ceiling Tiles

V3-SAHARA-22MEO

Fire Ratings	Class A
	Euroclass Rating B-s1-d0
	Flame Class V-0
Code Compliance	2015, 2012, 2009, and 2006 IBC
Indoor Air Quality	Greenguard Gold Certified; low-VOC; dust and fiber free
Moisture	FEMA Class 4 Material; waterproof; washable
Sustainability	100% recyclable

PERFORMANCE

Noise Reduction	NRC 0.15
	NRC 0.30 with Soniguard
Sound Transmission	STC 15
	STC 15 with AcoustoTherm
	STC 18 with Soniguard
Ceiling Attenuation	CAC 21
	CAC 26 with Soniguard
Light Reflectance	6.97%
Thermal Insulation	R-6.0 with Soniguard