

PRODUCT DATA SHEET

Sahara Sand Ceiling Tiles

V3-SAHARA-22SAO

SPECIFICATIONS

Height 23.875 in. **Width** 23.875 in.

Area 4 sq. ft. (nominal)

Features Project 0.11 in. from tile face


Collection Signature **Thickness** 0.030 in.

Weight 12.8 oz. (nominal)

Material Rigid vinyl

Color Sand Finish Satin

Recessed Yes, this style can be used **Lighting** with recessed lighting



INSTALLATION

Installation Type Standard drop (15/16 to 1 in.)

Slimline drop (9/16 in.)

Refacing

Glue-up (butt joint)

Borders Yes, this style can be trimmed for use along borders

Strips Required Yes, decorative strips or smooth strips required for glue-up installations

Direct Mount Grid Yes, this product can be used with direct mount grid

Temp. Warning Not recommended for installation where ceiling temperatures exceed 120°F

Sag Warning Some minor sagging can occur when used in full-size grid squares

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation Contact us for information



PRODUCT DATA SHEET

Sahara Sand Ceiling Tiles

V3-SAHARA-22SAO

Fire Ratings Class A

Euroclass Rating B-s1-d0

Flame Class V-0

Code Compliance 2015, 2012, 2009, and 2006 IBC

Indoor Air Quality Greenguard Gold Certified; low-VOC; dust and fiber free

Moisture FEMA Class 4 Material; waterproof; washable

Sustainability 100% recyclable

PERFORMANCE

Noise Reduction NRC 0.15

NRC 0.30 with Soniguard

Sound Transmission STC 15

STC 15 with AcoustoTherm

STC 18 with Soniguard

Ceiling Attenuation CAC 21

CAC 26 with Soniguard

Light Reflectance 83.88%

Thermal Insulation R-6.0 with Soniguard