


SPECIFICATIONS

| | |
|--------------------|--------------------------------|
| Height | 23.875 in. |
| Width | 23.875 in. |
| Area | 4 sq. ft. (nominal) |
| Features | Recess 0.50 in. from tile face |
| Collection | Feather-Light |
| Thickness | 0.013 in. |
| Weight | 6.4 oz. (0.10 lb. per sq. ft.) |
| Material | Transluminous rigid vinyl |
| Color | Frosted |
| Finish | Satin |
| Perforation | Available |



INSTALLATION

| | |
|--------------------------|--|
| Installation Type | Standard drop (15/16 to 1 in.) |
| Borders | Yes, this style may be trimmed for use along borders |
| Direct Mount Grid | Yes, this product may be used with direct mount grid |

CERTIFICATIONS, LISTINGS, APPROVALS

| | |
|------------------------------|---|
| Drop-out Installation | Yes, approved for installation <u>beneath</u> fire suppression sprinklers |
| | IAPMO Uniform ES Listing Report 5021 |
| | IAPMO Uniform ES Evaluation Report 0310 |
| | FM Class 4651 |
| | FM Certificate of Compliance |
| | NFPA 13 |
| | CertMark Evaluation Report CMI-ER31001 |



| | |
|---------------------------|---|
| Fire Ratings | Class A Euroclass Rating B-s2-d0 Flame Class V-0 |
| Code Compliance | 2015, 2012, 2009, and 2006 IBC |
| Indoor Air Quality | Greenguard Gold Certified; low-VOC; dust and fiber free |
| Food Preparation | FDA and USDA Compliant |
| Moisture | FEMA Class 4 Material; waterproof; washable |
| Sustainability | 100% recyclable |

PERFORMANCE

| | |
|----------------------------|--|
| Noise Reduction | NRC 0.25 NRC 0.30 with AcoustoTherm |
| Sound Transmission | STC 10 STC 11 with AcoustoTherm |
| Ceiling Attenuation | CAC 14 |
| Light Reflectance | 8.99% |
| Light Transmittance | 76.81% |
| Thermal Insulation | R-0.012 R-0.80 with AcoustoTherm |