


SPECIFICATIONS

Height	23.875 in.
Width	23.875 in.
Area	4 sq. ft. (nominal)
Features	Project 0.59 in. from tile face
Collection	Feather-Light
Thickness	0.013 in.
Weight	6.4 oz. (0.10 lb. per sq. ft.)
Material	Transluminous rigid vinyl
Color	Frosted
Finish	Satin
Cut-out	6 in. cut-out available



INSTALLATION

Installation Type	Standard drop (15/16 to 1 in.)
Borders	No, border tiles may be required
Direct Mount Grid	Yes, this product may be used with direct mount grid
Temp. Warning	Not recommended for installation where ceiling temperatures exceed 120°F

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation	Yes, approved for installation <u>beneath</u> fire suppression sprinklers
	IAPMO Uniform ES Listing Report 5021
	IAPMO Uniform ES Evaluation Report 0310
	FM Class 4651
	FM Certificate of Compliance
	NFPA 13

	CertMark Evaluation Report CMI-ER31001
Fire Ratings	Class A Euroclass Rating B-s2-d0 Flame Class V-0
Code Compliance	2015, 2012, 2009, and 2006 IBC
Indoor Air Quality	Greenguard Gold Certified; low-VOC; dust and fiber free
Moisture	FEMA Class 4 Material; waterproof; washable
Sustainability	100% recyclable

PERFORMANCE

Noise Reduction	NRC 0.25 NRC 0.30 with AcoustoTherm
Sound Transmission	STC 10 STC 11 with AcoustoTherm
Ceiling Attenuation	CAC 14
Light Reflectance	8.99%
Light Transmittance	76.81%
Thermal Insulation	R-0.012 R-0.80 with AcoustoTherm