

SPECIFICATIONS

Height	23.875 in.
Width	23.875 in.
Area	4 sq. ft. (nominal)
Features	Project 0.87 in. from tile face
Collection	Feather-Light
Thickness	0.013 in.
Weight	6.4 oz. (0.10 lb. per sq. ft.)
Material	Transluminous rigid vinyl
Color	Translucent
Finish	Satin



INSTALLATION

Installation Type	Standard drop (15/16 to 1 in.)
Borders	No, border tiles may be required
Direct Mount Grid	Yes, this product can be used with direct mount grid
Temp. Warning	Not recommended for installation where ceiling temperatures exceed 120°F

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation	Yes, approved for installation <u>beneath</u> fire suppression sprinklers
	IAPMO Uniform ES Listing Report 5021
	IAPMO Uniform ES Evaluation Report 0310
	FM Class 4651
	FM Certificate of Compliance
	NFPA 13
	UL File R4036



PRODUCT DATA SHEET
Florentine Translucent Ceiling Tiles

V1-FLOREN-22WTT

Fire Ratings	Class A Euroclass Rating B-s2-d0 Flame Class V-0
Code Compliance	2015, 2012, 2009, and 2006 IBC
Indoor Air Quality	Greenguard Gold Certified; low-VOC; dust and fiber free
Moisture	FEMA Class 4 Material; waterproof; washable
Sustainability	100% recyclable

PERFORMANCE

Noise Reduction	NRC 0.25 NRC 0.30 with AcoustoTherm NRC 0.50 with Soniguard
Sound Transmission	STC 10 STC 11 with AcoustoTherm STC 13 with Soniguard
Ceiling Attenuation	CAC 14 CAC 20 with Soniguard
Light Reflectance	49.91%
Light Transmittance	31.62%
Thermal Insulation	R-0.012 R-0.80 with AcoustoTherm R-6.0 with Soniguard