

MANUFACTURER INFORMATION	
MANUFACTURER'S NAME & TELEPHONE	Manufactured for Ceilume by Vita Nonwovens – (336) 431-7187
STREET ADDRESS	2215 Shore Street
CITY / STATE / ZIP	High Point, NC 27263

SECTION 1 – PRODUCT IDENTIFICATION	
PRODUCT NAME	Soniguard Drop Ceiling Insulation – 25 squares
CHEMICAL FAMILY	Polyethylene terephthalate (PET) and modified PET polymer, CAS 25038-59-9
CHEMICAL NAME	Finished goods-commodities
MSDS NUMBER	MSDS 006
HMIS	HEALTH – 1 FLAMMABILITY – 1 REACTIVITY – 0

SECTION 2 – HAZARDOUS INGREDIENTS
None

SECTION 3 – PHYSICAL DATA	
APPEARANCE	Solid
COLOR	Will vary with the addition of pigments
ODOR	Negligible
SOLUBILITY IN WATER	Insoluble
% VOLATILE BY VOLUME	Trace amounts

**SECTION 4 – FIRE AND EXPLOSION DATA**

<b>FLASH POINT</b>	Solid Material > 200°F
<b>EXTINGUISHING MEDIA</b>	Water, foam, and dry chemical
<b>SPECIAL FIRE FIGHTING PROCEDURES / UNUSUAL FIRE OR EXPLOSION HAZARDS</b>	All fire fighters should wear full emergency equipment, with a self-contained breathing apparatus, and full protective clothing. During a fire, irritating vapors and toxic gases may be generated.

**SECTION 5 – HEALTH EFFECTS DATA**

<b>HUMAN EFFECTS OF OVEREXPOSURE</b>	No adverse health effects have been observed. Human experience indicates no irritation upon skin contact with PET fiber.
--------------------------------------	--------------------------------------------------------------------------------------------------------------------------

**SECTION 6 – FIRST AID**

<b>EYES</b>	Irrigate immediately with water for at least 5 minutes. Mechanical effects only.
<b>SKIN</b>	No adverse effects anticipated by this route of exposure incidental to proper industrial handling.
<b>INHALATION</b>	Remove to fresh air.

**SECTION 7 – PERSONAL PROTECTION RECOMMENDATIONS**

Safety glasses are advisable when cutting fiber. Adequate ventilation and respiratory protection is recommended when cutting fiber with a hot wire or when flame laminating.

**SECTION 8 – REACTIVITY DATA**

<b>STABILITY</b>	Stable
<b>POLYMERIZATION</b>	Will not occur
<b>INCOMPATIBILITY (MATERIALS TO AVOID)</b>	None
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b>	Burning fiber may produce toxic decomposition products including carbon monoxide, carbon dioxide, acetaldehyde, and other harmful products.

**SECTION 9 – SPILL OR LEAK PROCEDURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Collect as normal combustible solid waste

**WASTE DISPOSAL METHOD**

Conform to local, state, and federal regulations for non-hazardous wastes

**SECTION 10 – TRANSPORTATION**

**DOT REGULATION**

Not regulated

**SECTION 11 – SPECIAL PRECAUTIONS AND STORAGE DATA**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Storage of product prior to use in areas equipped with sprinkler systems may be required by local code or for insurance.

Do not expose fiber to open flames, burning cigarettes, space heaters, naked lights, or other sources of intense heat. If ignited, fiber can burn, consuming oxygen and producing toxic gases.

No special handling is required, storage in a dry and well-ventilated indoor location is recommended.

**SECTION 12 – ADDITIONAL INFORMATION**

The information supplied herein is presented in good faith and believed to be accurate to the best knowledge of Ceilume®. However, since conditions of use are beyond our control, Ceilume® makes no warranties, expressed or implied, as to the use of this information or the fitness of this product for a particular purpose.